

Juniper Networks T1 Mini-PIM



The Juniper Networks optional single-port T1 Mini Physical Interface Modules (Mini-PIM) for the SSG 20 platform complement the five on-board 10/100 Ethernet interfaces with expanded WAN connectivity. The T1 Mini-PIMs include one physical T1 port with an integrated CSU/DSU.

The combination of a T1 modem and an integrated CSU/DSU eliminates the need to deploy several separate external devices, thereby consolidating devices to reduce capital expenditures, saving valuable space and simplifying management.

Features

- Fully integrated CSU/DSU
- Full and fractional T1 capabilities
- 56K & 64K modes support
- ANSI T1.102, T1.107, T1.403 T1 support
- Independent Clock
- Loopback, BERT, FDL, and Long Buildout diagnostics
- Complete configuration and management by CLI, WebUI, or NetScreen Security-Manager

Specifications

Product Number	Description
JXM-1T1-S	1 port T1 Mini Physical Interface Module

ScreenOS Software Release

The T1 Mini PIM is supported in ScreenOS 5.4 on the SSG 20

Network Interface Specifications

Transmit bit rate:	1.544 Mbps
Receive bit rate:	1.544 Mbps
Line encoding:	AMI B8ZS
Modes:	Framed Clear Channel Fractional
Framing:	Superframe (D4/SF) Extended Superframe (ESF)

HDLC Features

- N x 64 Kbps or N x 56 Kbps, nonchannelized data rates (T1:N = 1 to 24)
- CRC 16/32
- Shared Flag
- Idle flag/fill
- Counters: Runts, Giants, FCS, Error, Abort Error, Align Error

Interface Connector

- RJ-48

System timing

- External (network recovered clocks)

Dimensions (W x L x H) and Weight

- 3.75" x 5.9" x 0.80"
- 9.5 cm x 14.5 cm x 2.0 cm
- 0.18 lb. (81.6g)

Environmental

Operating temperature: 0-40°C
 Storage temperature: -40 to 70°C
 Relative humidity: 5% to 90% non-condensing

Loopback Diagnostics

- Local, Remote, Payload
- Test patterns (BERT)
- All ones
- All zeros
- Alternating ones and zeros (AA/55)
- 1:3 or 1 in 4 pattern
- 1:7 or 1 in 8 pattern
- 3:24 - 3 bits set in every 24 bits
- QRSS20 (Modified PRBS 2^20-1, with 14 zero suppression)
- PRBS 2^7-1
- PRBS 2^9-1 (as specified in ITU-T O.153)
- PRBS 2^11-1 (as specified in ITU-T O.153)/2047 pattern
- PRBS 2^15-1 (as specified in ITU-T O.151/O.153)
- PRBS 2^20-1 (as specified in ITU-T O.153)
- Programmable word or 32-bit programmable pattern
- Network (T1) alarms
- LOS, LOF, AIS, YLW

Error Counters

- Controlled Slipped Seconds (CSS or CS)
- Line Errored Seconds (LES)
- Errored Seconds (ES)
- Bursty Errored Seconds (BES)
- Severely Errored Seconds (SES)
- Severely Errored Framing Seconds (SEFS)
- Loss Of Signal Seconds (LOS)
- Loss Of Framing Seconds (LOFS)
- UAS Unavailable Seconds (UAS)

LEDs

PIM LED's indicate port status with the following LED states:

- Alarm – Solid Yellow
- Loopback – Solid Yellow when loopback enabled
- CD (Carrier Detect) – solid green when line is sync'ed

Standards and Compliance

Agency/Regulatory Compliance

Safety

- CAN/CSA-C22.2 No. 60950-1-03/UL 60950-1 Third Edition, Safety of Information Technology Equipment
- EN 60950-1:2001 + A11, Safety of Information Technology Equipment
- IEC 60950-1:2001 First Edition, Safety of Information Technology Equipment

EMC (Emissions)

- FCC Part 15 Class B
- EN 55022 Class B
- AS/NZS 3548 Class B
- VCCI Class B

Immunity

- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity

ETSI

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility

Telecom

- FCC Part 68/TIA-968
- IC CS-03

T1 Standards

- ANSI T1.102
- ANSI T1.107
- ANSI T1.403
- Telcordia GR-499-CORE



CORPORATE HEADQUARTERS
AND SALES HEADQUARTERS
FOR NORTH AND SOUTH AMERICA
Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, CA 94089 USA
Phone: 888-JUNIPER (888-586-4737)
or 408-745-2000
Fax: 408-745-2100
www.juniper.net

EAST COAST OFFICE
Juniper Networks, Inc.
10 Technology Park Drive
Westford, MA 01886-3146 USA
Phone: 978-589-5800
Fax: 978-589-0800

ASIA PACIFIC REGIONAL
SALES HEADQUARTERS
Juniper Networks (Hong Kong) Ltd.
Suite 2507-11, Asia Pacific Finance Tower
Citibank Plaza, 3 Garden Road
Central, Hong Kong
Phone: 852-2332-3636
Fax: 852-2574-7803

EUROPE, MIDDLE EAST, AFRICA
REGIONAL SALES HEADQUARTERS
Juniper Networks (UK) Limited
Juniper House
Guildford Road
Leatherhead
Surrey, KT22 9JH, U. K.
Phone: 44(0)-1372-385500
Fax: 44(0)-1372-385501

Copyright 2006, Juniper Networks, Inc. All rights reserved. Juniper Networks and the Juniper Networks logo are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered trademarks, or registered service marks in this document are the property of Juniper Networks or their respective owners. All specifications are subject to change without notice. Juniper Networks assumes no responsibility for any inaccuracies in this document or for any obligation to update information in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.